

```
PicoMite MMBasic RP2040 Edition V6.00.01RC9
OPTION SYSTEM SPI GP10,GP11,GP24
OPTION SYSTEM I2C GP4,GP5
OPTION FLASH SIZE 4194304
OPTION COLOURCODE ON
OPTION HEARTBEAT OFF
OPTION PICO OFF
OPTION CPUSPEED 252000 'KHz
OPTION DISPLAY 43, 89
OPTION LCDPANEL ST7789_135, LANDSCAPE,GP8,GP12,GP9,GP25
OPTION SDCARD GP23, GP18, GP19, GP20
OPTION PLATFORM RP2040-GEEK
> freepins
GP 0    1    OFF
GP 1    2    OFF
GP 2    4    OFF
GP 3    5    OFF
GP 4    6    Boot Reserved : SYSTEM I2C SDA
GP 5    7    Boot Reserved : SYSTEM I2C SCL
GP 6    9    OFF
GP 7    10   OFF
GP 8    11   Boot Reserved : LCD DC
GP 9    12   Boot Reserved : LCD CS
GP10   14   Boot Reserved : SPI SYSTEM CLK
GP11   15   Boot Reserved : SPI SYSTEM MOSI
GP12   16   Boot Reserved : LCD Reset
GP13   17   OFF
GP14   19   OFF
GP15   20   OFF
GP16   21   OFF
GP17   22   OFF
GP18   24   Boot Reserved : SD CLK
GP19   25   Boot Reserved : SD MOSI
GP20   26   Boot Reserved : SD MISO
GP21   27   OFF
GP22   29   OFF
GP23   41   Boot Reserved : SD CS
GP24   42   Boot Reserved : SPI SYSTEM MISO
GP25   43   Boot Reserved : LCD BACKLIGHT
GP26   31   OFF
GP27   32   OFF
GP28   34   OFF
GP29   44   OFF
```