

# Super High Efficiency (SHE) rectifier for Telecom applications

The Flatpack2 48/2000 Super HE is contributing to setting the new industry standard for efficiency in the DC power market.

With an efficiency of 97.8% the Super HE is a premium rectifier particularly suitable for markets and applications where the energy is costly. In grid connected applications the payback time is down to 2 years compared to standard HE rectifiers, and in hybrid applications even faster.

The Flatpack2 2000/48 Super HE is fully compatible with Flatpack2 and Flatpack2 HE systems and can replace any 2kW Flatpack2 module.



## Flatpack2 48V SHE Rectifier

48 / 2000 SHE

Doc: EDM0000109001

### APPLICATIONS

#### TELECOM - WIRELESS

- Radio base station / Cell sites
- LTE / 4G / WiMAX
- Mobile switching center (MCS)
- Microwave
- Broadband

#### TELECOM - FIXED

- Central office
- Telephony servers / switches
- Fiber optics
- Microwave
- Broadband
- Broadcast
- Data center



6U 300A power core with Smartpack S controller



Flatpack2 power core in T3 Outdoor cabinet

### KEY FEATURES

- SUPER HIGH EFFICIENCY – 97.8%
- HIGH POWER DENSITY – 22 W/IN3
- COMPATIBLE WITH EXISTING SYSTEMS
- GLOBAL COMPLIANCE
- PATENTED TECHNOLOGY
- HOT PLUGGABLE



9U hybrid power core with Smartpack2 controller

# Flatpack2 48V Super HE



Doc: EDM0000109001

Model	48/2000 SHE
Part number	241115.106
<b>INPUT DATA</b>	
Voltage (nominal range)	185 - 264 V <sub>AC</sub>
Voltage (operating range)	85 - 264 V <sub>AC</sub>
Frequency	45 - 66 Hz
Maximum current	11.6 A <sub>RMS</sub>
Protection	Fuse, varistor for transient protection, shutdown when V <sub>IN</sub> is out of range
<b>OUTPUT DATA</b>	
Voltage (default)	53.5 V <sub>DC</sub>
Voltage (adjustable range)	43.5 <sup>1)</sup> - 57.6 V <sub>DC</sub>
Max power, nominal input	2000 W
Max power, de-rated @V <sub>IN</sub> = 85 V <sub>AC</sub>	850 W
Max current, @V <sub>OUT</sub> = 48 V <sub>DC</sub>	41.7 A
Current sharing	±5.0% of max current
Static voltage regulation (10-100% load)	±0.5%
Dynamic voltage regulation	±5.0% for 10-90% or 90-10% load variation, regulation time < 50ms
Hold up time (2000W load)	>10ms; output voltage > 42 V <sub>DC</sub>
Ripple	< 150 mV <sub>PP</sub> , 30 MHz bandwidth
Protection	Overvoltage shutdown, short circuit proof, high temperature, hot plug-in inrush current limiting, fuse
<b>OTHER SPECIFICATIONS</b>	
Peak Efficiency	97.8 %
Isolation	3.0 kV <sub>AC</sub> – input to output 1.5 kV <sub>AC</sub> – input to protective earth 0.5 kV <sub>DC</sub> – output to protective earth
Alarms (Red LED)	Low mains shutdown, High and low temperature shutdown, Rectifier Failure, Overvoltage shutdown on output, Fan failure, Low voltage alarm, CAN bus failure
Warnings (Yellow LED)	Rectifier in power derate mode, Remote current limit activated, Input voltage out of range, flashing at overvoltage
Normal (Green LED)	Input and output ok
MTBF (Telcordia SR-332 Iss.3 method II Case L1)	1 900 000 hours
Operating temperature (5 - 95% RH non-cond.)	- 25 – 75°C [-13 – 167°F ]
Max output power de-rates above temp / to	45°C [+113°F] / 1350 W
Storage temperature	-40 to +85°C (-40 to +185°F), humidity 0 - 99% RH non-condensing
Dimensions[WxHxD] / Weight	109 x 41.0 x 327mm [4.25 x 1.61 x 13"] / 2.050 kg [4.3lbs]
<b>DESIGN STANDARDS</b>	
Electrical safety	EN 60950-1:2006+A11:2009+A1:2010+A12:2011, UL 60950-1:2011
EMC	EN 61000-6-1:2007, -6-2:2005, -6-3:2007 + A1:2011, -6-4:2007 + A1:2011 EN 300 386:v1.6.1, FCC CFR 47 Part 15:2013
Environment	ETSI EN 300 019: 2-1 (Class 1.2), 2-2 (Class 2.3) & 2-3 (Class 3.2) 2011/65/EU (RoHS) & 2012/19/EU (WEEE)

1) Stand-by / test operation (V<sub>OUT</sub> < 48V<sub>DC</sub>) limited for V<sub>IN</sub> > 230 V<sub>AC</sub>